

# Contents

<b>Acknowledgments</b> . . . . .	iii
<b>Abstract</b> . . . . .	iv
<b>List of Tables</b> . . . . .	viii
<b>List of Figures</b> . . . . .	ix
<b>1. Introduction</b> . . . . .	1
1.1. Cooperative Networks . . . . .	2
1.2. IEEE 802.11 . . . . .	2
1.2.1. Distributed Coordination Function (DCF) . . . . .	3
1.2.2. Point Coordination Function (PCF) . . . . .	5
1.3. Background and literature work . . . . .	5
<b>2. Proposed Partner Choosing Algorithms</b> . . . . .	8
2.1. Static partner choosing algorithm in PCF . . . . .	10
2.2. Dynamic partner choosing algorithm in PCF . . . . .	16
<b>3. Simulation and Numerical Results</b> . . . . .	26
3.1. Simulation Results . . . . .	26
3.2. Summary . . . . .	36

<b>4. Conclusion</b> . . . . .	38
<b>Bibliography</b> . . . . .	40



# List of Tables

3.1. Simulation parameters . . . . .	27
--------------------------------------	----



# List of Figures

1.1. Structure in IEEE 802.11 MAC . . . . .	3
1.2. IEEE 802.11 DCF Operation . . . . .	5
1.3. IEEE 802.11 PCF Process . . . . .	6
2.1. The Process of Whisper . . . . .	10
2.2. The Process of Help . . . . .	10
2.3. The Format of 802.11 Association Request Message . . . . .	11
2.4. How to Choose Helper . . . . .	12
2.5. The Form of The Helper Structure . . . . .	12
2.6. An Example Scenario . . . . .	15
2.7. The Helper Structure of Station 1 . . . . .	16
2.8. The Helper Structure of Station 3 . . . . .	17
2.9. The Helper Structure of Station 6 . . . . .	18
2.10. The Best Condition After Choosing (Helper, Under) Pair . . . . .	19
2.11. Station 1 Has a Bad Channel and Choose a Helper . . . . .	21
2.12. Station 6 Has a Bad Channel and Choose a Helper . . . . .	22

2.13. The Channel Between Station 6 and 5 Becomes Poor . . . . .	23
2.14. Station 2 Turns to Bad State . . . . .	24
2.15. Station 3 and 6 Have to Change Their ( Helper, Under ) Pair . . . . .	25
3.1. The Simulation Topology . . . . .	27
3.2. The Error Model . . . . .	28
3.3. The Topology of The First Part Simulations . . . . .	29
3.4. The Throughput Results of PCF, Static Cooperative PCF, and Dynamic Co- operative PCF . . . . .	30
3.5. The Delay Results of PCF, Static Cooperative PCF, and Dynamic Coopera- tive PCF . . . . .	30
3.6. The Packet Loss Ratio Results of PCF, Static Cooperative PCF, and Dynamic Cooperative PCF . . . . .	31
3.7. The Throughput Results of PCF, Static Cooperative PCF, and Dynamic Co- operative PCF With Packet Error Rate 0.3 . . . . .	33
3.8. The Delay Results of PCF, Static Cooperative PCF, and Dynamic Coopera- tive PCF With Packet Error Rate 0.3 . . . . .	33
3.9. The Packet Loss Ratio Results of PCF, Static Cooperative PCF, and Dynamic Cooperative PCF With Packet Error Rate 0.3 . . . . .	34
3.10. The Distribution of The Load of Help Among All The Stations . . . . .	36